



"RUPI CABLE- AND WIRE STOCKINGS,  
SIMPLY BRILLIANT AND INDISPENSABLE"

# RUPI-COLOGNE<sup>®</sup>, INC.

**YOUR SPECIALIST AROUND CABLE AND WIRE**

## Cable and rope joining stockings

### >> RP- 400



These stockings are designed for joining cables or ropes with the same diameter and without a lot of twist. This way it is, for example, possible to change crane ropes in one run or to include two cable lengths at once. In case of increased torsion of the cables etc. we recommend using single stockings together with respective whirl shackles to compensate for the twist. This mesh of galvanized steel braids is woven with two strands, open on both ends and has no eyelets.



(2-layered / standard)



(3-layered / enhanced)

#### **RP-400:**

Available in standard lengths 1500 mm, 2000 mm and 3000 mm. Other lengths upon request!

Also available in the following design:

>> **STAINLESS STEEL (STAINLESS STEEL BRAIDING)**

>> **STRAINED BOWDEN CABLE**

>> **STAINLESS STEEL REINFORCED** (three-layer design for higher tensile strength)

>> **PLASTIC COATED STRANDS**



#### **rupi-Cologne, Inc.**

2100 Skyline View Lane  
NIXA, MO 65714  
U.S.A.

#### **Phone + Fax**

1-417-883-9939  
1-417-883-9949

#### **E-mail + Web**

info@rupi-cologne-inc.com  
www.rupi-cologne-inc.com



"RUPI CABLE- AND WIRE STOCKINGS,  
SIMPLY BRILLIANT AND INDISPENSABLE"

**RUPI-COLOGNE<sup>®</sup>, INC.**

**YOUR SPECIALIST AROUND CABLE AND WIRE**

## Cable and rope joining stockings

### >> RP- 400

For cables and ropes with $\varnothing$ from - to	Permissible tension load in kN / tons approx.	Thimble size for bolt $\varnothing$ approx. mm	Part number <small>Please indicate required length/s (e.g. RP- 410-1500) for stocking length 1500</small>
06 - 08 mm	3,60 / 0,37	both sides open	RP - 406 - + length
08 - 10 mm	3,60 / 0,37	both sides open	RP - 408 - + length
10 - 15 mm	5,12 / 0,52	both sides open	RP - 410 - + length
15 - 20 mm	6,93 / 0,71	both sides open	RP - 415 - + length
20 - 30 mm	8,67 / 0,88	both sides open	RP - 420 - + length
30 - 40 mm	10,40 / 1,06	both sides open	RP - 430 - + length
40 - 50 mm	21,36 / 2,18	both sides open	RP - 440 - + length
50 - 60 mm	21,36 / 2,18	both sides open	RP - 450 - + length
60 - 80 mm	28,48 / 2,90	both sides open	RP - 460 - + length
80 - 100 mm	45,60 / 4,65	both sides open	RP - 480 - + length
100 - 120 mm	50,67 / 5,17	both sides open	RP - 4100 - + length



**Greater loads and higher tensile forces  
and special designs on request.  
Produceable immediately.**

#### rupi-Cologne, Inc.

2100 Skyline View Lane  
NIXA, MO 65714  
U.S.A.

#### Phone + Fax

1-417-883-9939  
1-417-883-9949

#### E-mail + Web

info@rupi-cologne-inc.com  
www.rupi-cologne-inc.com