

YOUR SPECIALIST AROUND CABLE AND WIRE

Overhead cable stockings >> RP- 500



Köln seit

idn.

Overhead cable insertion stockings are used for the efficient pulling of copper, aluminium and steelaluminium ropes in overland cable construction. The specially woven mesh of triple strands guarantees maximum safety and force-fitting to the material to be pulled. The flexi-

ble and pressed-on eye ensures an unproblematic unrolling of the stocking. Of course, these stockings can also be used on cranes, excavators and lifts.





(3-layered / standard)

RP-500:

Available in standard lengths 1250 mm, 1500 mm and 2000 mm. Other lengths upon request! Also available in the following design:

- >> STAINLESS STEEL (STAINLESS STEEL BRAIDING)
- >> STAINLESS STEEL REINFORCED (three-layer design for higher tensile strength)
- >> STRAINED BOWDEN CABLE
- >> PLASTIC COATED STRANDS

16



rupi-Cologne, Inc.	Phone + Fax	E-mail + Web
2100 Skyline View Lane	1-417-883-9939	info@rupi-cologne-inc.com
NIXA, MO 65714	1-417-883-9949	www.rupi-cologne-inc.com
U.S.A.		

We strictly sell goods under our terms and conditions. Mistakes as well as misprints reserved.

"RUPI CABLE- AND WIRESTOCKINGS. SIMPLY BRILLIANT AND INDISPENSABLE"

YOUR SPECIALIST AROUND CABLE AND WIRE

Overhead cable stockings >> RP- 500

rupi Köln seit 1966

For cables and ropes with ø from - to	Permissible tension load in kN / tons approx.	Thimble size for bolt ø approx. mm	Part number Please indicate required length/s (e.g. RP- 510-1500) for stocking length 1500
08 - 15 mm	7,68 / 0,78	flexible rope eyelets	RP - 510 - + length
15 - 20 mm	10,40 / 1,06	flexible rope eyelets	RP - 515 - + length
20 - 30 mm	13,00 / 1,33	flexible rope eyelets	RP - 520 - + length
30 - 40 mm	15,60 / 1,59	flexible rope eyelets	RP - 530 - + length
40 - 50 mm	32,04 / 3,27	flexible rope eyelets	RP - 540 - + length
50 - 60 mm	32,04 / 3,27	flexible rope eyelets	RP - 550 - + length
60 - 70 mm	42,72 / 4,36	flexible rope eyelets	RP - 560 - + length
70 - 80 mm	42,72 / 4,36	flexible rope eyelets	RP - 570 - + length
80 - 100 mm	68,40 / 6,97	flexible rope eyelets	RP - 580 - + length
100 - 120 mm	76,00 / 7,75	flexible rope eyelets	RP - 5100 - + length

Greater loads and higher tensile forces and special designs on request. Produceable immediately.

rupi-Cologne, Inc.	Phone + Fax
2100 Skyline View Lane	1-417-883-9939

2100 Skyline View Lane NIXA, MO 65714 U.S.A. 1-417-883-9939 1-417-883-9949

E-mail + Web

info@rupi-cologne-inc.com www.rupi-cologne-inc.com 17

We strictly sell goods under our terms and conditions. Mistakes as well as misprints reserved.